


Burris TectView EX Series VINYL



Innovative and enhanced security and privacy features for your customer's peace of mind.

Double-Hung



Enhanced Security and Privacy

Give your customers more peace of mind with innovative security and privacy features. Double- and single-hung windows are designed with an interlocking checkrail, steel hardware reinforcement and a unique anti-jar sill.

Stronger Frames Than Ordinary Vinyl

Our precision welding process creates more durable products that resist warping or twisting over time. Burris TectView EX Series window frames are 52% stronger than ordinary vinyl.¹

Fade-Resistant Vinyl Formula

Burris TectView EX Series is made of high-grade vinyl that resists yellowing and never needs painting. The solid color throughout the vinyl keeps minor dings and scratches virtually invisible. Solid-color frames are available in White, Almond and Fossil.

Exclusive Weather Protection System

Protect your home with our exclusive weather repel system on single- and double-hung windows. It has three points of protection to channel water away from the home — including triple weatherstripping.

Energy-Efficient Multichambered Frame

Our vinyl frame has up to 12 insulating air chambers inside — significantly more than ordinary vinyl — to keep homes warmer in the winter and cooler in the summer.

Durable Laminate Exterior Finish

Dual-color frame options offer White interior with Black laminate exterior. Our vinyl laminate is 2.6x more durable than painted vinyl.²

Free-form Mulling Capabilities

Create a large or unique combination for your project by mulling standard and custom-sized windows together. Combinations are factory-mulled and arrive ready for installation.³

Optional Performance Enhancements

Increase structural strength with optional performance enhancements such as steel reinforcement.

Additional Features and Options

We have the features and options that fit most any project. Choose from multiple frame types, several grille options and a full lineup of window styles.

Limited Lifetime Warranty

Burris products are backed by a limited lifetime warranty. Please speak with your local sales representative for more details.

Testing Beyond Requirements

At Burris, our TectView EX Series products are tested beyond requirements to help ensure long-lasting performance and reduce callbacks for you.

Available in these window styles:

Special shapes also available.



Awning Window



Casement Window



Single-Hung Window



Double-Hung Window



Fixed Window



Sliding Window

^{1,2,3} See back cover for disclosures.


Product Specifications

WINDOW & PATIO DOOR STYLES	MIN. WIDTH	MIN. HEIGHT	MAX. WIDTH	MAX. HEIGHT	PERFORMANCE CLASS & GRADE	PERFORMANCE VALUES			TDI #	FRAME / INSTALL
						U-FACTOR	SHGC	STC		
Awning Dual-Pane Vent	16"	14-½"	59-½"	43-½"	LC-PG35 - LC-PG50	0.24 - 0.32	0.11 - 0.25	30	FL26533	Block Frame Nail Fin
Casement Dual-Pane Vent	14-½"	17-½"	35-½"	71-½"		0.23 - 0.32	0.11 - 0.25	30-33	FL26534	
Sliding Window Dual-Pane, 2-Panel	21-½"	11-½"	96"	72"	R-PG25 - R-PG50	0.23 - 0.34	0.11 - 0.29	25	FL16809	
Sliding Window Dual-Pane, 3-Panel	47-½"	11-½"	120"	72"	R25 - R50	0.23 - 0.34	0.11 - 0.29	25	FL16809	
Double-Hung Dual-Pane Vent	14-½"	23-½"	53-½"	86" ⁸	R-PG20 - R-PG50	0.24 - 0.32	0.12 - 0.28	26	FL16813	
Single-Hung Dual-Pane Vent	14-½"	23-½"	53-½"	96" ⁹	R-PG25 - R-PG50	0.23 - 0.35	0.13 - 0.29	25	FL16812	
Fixed Frame Rectangle Dual-Pane	10" ⁶	10" ⁶	108" 40 sq. ft. max.	108" 40 sq. ft. max.	CW-PG30 - CW-PG50	0.21 - 0.33	0.14 - 0.32	26	FL16811	

Window sizes available in 1⁄8" increments
Special sizes available. See your rep for more details.
Visit burris.com for specific sizes and glazings tested and for more information regarding frame and installation types.

Glass & Additional Energy Efficiency Upgrades


Low-E Glass



Low-E 270 insulating dual-pane glass with argon




Low-E 366 insulating dual-pane glass with argon




Low-E 340 insulating dual-pane glass with argon

Additional Glass Options



Tempered glass



High Altitude Low-E




Obscure Low-E

Colors

Frame Colors

Create a signature look with solid-color and dual-color frames. Dual-color frames allow you to choose a different color for the exterior with a White interior.

Solid-Colors:



White



Almond



Fossil

Dual-Color Frames:⁴



Black

Grilles

Grilles

Grilles are color-matched to your window interior and exterior frame color.



Grilles-Between-the-Glass
FLAT BAR
3/16" x 5/8"⁵



Grilles-Between-the-Glass
CONTOUR
8 x 18MM⁵

Window Hardware


Casement & Awning

Folds neatly out of the way so it won't interfere with roomside window treatments. Finishes match interior frame colors.



Fold-Away Crank

Color-Matched Finishes:



White



Almond



Fossil


Sliding, Single- & Double-Hung

Cam-action locks pull the sashes against the weatherstripping for a tighter seal.



Cam-Action Lock

Color-Matched Finishes:



White



Almond



Fossil

Window Limited Opening Devices

A vent stop can be engaged or disengaged manually and restricts how far the bottom sash of a single- or double-hung window can open. A window opening control device (WOCD) complies with a safety standard and allows for ventilation, emergency escape and rescue when released. A WOCD automatically limits the sash opening to less than four inches, unless it is intentionally disengaged, enabling the sash to fully open. Stainless steel limited opening devices are available on casement and awning windows, and WOCDs are available on casement windows.




Vent Stop



Window Opening Control Device

Color-Matched Finishes:



White



Almond



Fossil

^{4,5} See back cover for disclosures.



burriswindows.com

NOTE: Product specifications may change without notice.

Actual colors may vary from those shown and products may vary slightly from illustrations and photos

¹ Based on the force required to bend a window frame profile.

² The abrasion resistance of Burris painted and laminate vinyl samples were tested and coatings compared in their ability to withstand a volume of abrasive materials using test method of ASTM D968.

³ Actual mullion span and combination size availability depends on design pressure requirements. Consider combination size, weight, and jobsite handling during design.

⁴ Exterior is an applied color, not an extruded color.

⁵ Appearance of exterior grille color may vary depending on the Low-E insulating glass selection.